



过滤组合 FILTRATION COMBO QSF



Maximum working pressure:

250kpa/36psi/2.5bar

Factory testing pressure:

400kpa/58psi/4.0bar

Size of silica sand:

0.5~0.8mm

Maximum water temperature:

43°C

Filtration combo are easy to use and install. Fiberglass reinforced tank with unequaled strength and durability.

These systems equipped with top-mount filter and centrifugal pump.



最大工作压力:

250kpa/36psi/2.5bar

工厂测试压力:

400kpa/58psi/4.0bar

石英砂规格: 0.5~0.8mm

最高操作温度: 43°C

一体化过滤系统, 使用简单, 安装方便, 缸体材质选用加固纤维, 因此这种产品坚固而耐用。

这个系统配备了顶出砂缸及循环过滤泵。

过滤组合是泳池和养鱼池的最佳选择

Filtration combo are the most recommendable equipment for swimming pool and fish pond.



立体标牌

Three-dimensional nameplate

Specification and size:

技术参数及产品尺寸

Model 型号	Sand Filter Model 砂缸型号	Pump Model 泵型号	Valve Size 接口尺寸 (mm)	Design Flow 设计流量 (m ³ /h)	Silica Sand 石英砂 (kg)	A (mm)	B (mm)	C (mm)
QSF400-6W	Q400	ABS033	40	6.48	30	760	759	175
QSF450-6W	Q450	ABS050	40	8.10	45	760	813	210
QSF500-6W	Q500	ABS100	40	11.10	80	760	856	235
QSF650-6W	Q650	ABS150	40	15.60	130	760	961	300

